

CP-24

CHLORINATED POLYOLEFIN — SPECIALTY ADDITIVE/ MODIFIER

DESCRIPTION

CP-24 is a water based dispersion of a chlorinated polyolefin. It has been engineered to perform as a modifier for coatings specializing in plastics applications, with indexes as high as 40%-- depending on the amount of adhesion the potential application requires.

APPLICATIONS

Modifier and adhesion promoter for difficult to adhere to substrates including plastics

FORM

Single Component, Air Dry Modifier

OPERATING DATA

- 1) Designed for Priming Applications because of color
- 2) For use as supplied (no viscosity reduction needed)
- 3) Predictable drying characteristics

CAUTION

Agitate prior to use.

TYPICAL PROPERTIES

Viscosity (Gardner-Holt)	10-400 cps
Color	Off White
Acid Value	-----
Solids (+/- 2)	20-24
Solvent	Water (Zero VOC)

PRECAUTIONS

Some materials in this product may cause skin and eye irritation and/or sensitization or other allergic responses upon repeated contact. Therefore this product must be handled with extreme care and in strict adherence to good industrial hygiene practices. Before using it or any other product referred to in this bulletin, consult the applicable Material Safety Data Sheets for appropriate handling procedures and protective equipment.

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, IS TO THE BEST OF OUR KNOWLEDGE TRUE AND ACCURATE. NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED IS MADE REGARDING THE PERFORMANCE OF ANY PRODUCT, SINCE THE MANNER OF USE IS BEYOND OUR CONTROL. NO SUGGESTION FOR PRODUCT USE, NOR ANYTHING HEREIN, SHALL BE CONSTRUED AS A RECOMMENDATION FOR ITS USE IN INFRINGEMENT OF ANY EXISTING PATENT

US Polymers-Accurez, LLC | 300 East Primm Street | St. Louis, MO 63111 | 314-638-1632 | FAX 314-638-3100 | www.uspolymers.com