

Epi-Tex[®] 120 HF

STANDARD & HIGH VISCOSITY VERSIONS

DESCRIPTION

Epi-Tex[®] 120 HF is the supreme epoxy ester in the Epi-Tex[®] line. Due to the selection of a superior oxidizing fatty acid, Epi-Tex[®] 120 HF offers adhesion, weatherability and resistance properties that are outstanding.

Epi-Tex[®] 120 HF also offers excellent color in an ester system

TYPICAL PROPERTIES

	STANDARD	HIGH SOLIDS
Viscosity (Gardner-Holdt)	W-Z	Z-Z3
- Reduced 50—40% in Aromatic 100	L-S	-----
- Reduced 45—40% in Aromatic 100	-----	U-X
Nonvolatile	50± 1%	45± 1%
Color	6 Max	6 Max
Wt./Gal. (pounds)	7.95± 0.15	7.7± 0.15
Acid Value	1.0 Max	1.0 Max
Solvent	Aromatic 100	Aromatic 100

PRECAUTIONS

This product is flammable. Some materials in this product may cause skin and eye irritation and/or sensitization or other allergic responses upon repeated contact. Therefore this product must be handled with extreme care and in strict adherence to good industrial hygiene practices. Before using it or any other product referred to in this bulletin, consult the applicable Material Safety Data Sheets for appropriate handling procedures and protective equipment.

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, IS TO THE BEST OF OUR KNOWLEDGE TRUE AND ACCURATE. NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED IS MADE REGARDING THE PERFORMANCE OF ANY PRODUCT, SINCE THE MANNER OF USE IS BEYOND OUR CONTROL. NO SUGGESTION FOR PRODUCT USE, NOR ANYTHING HEREIN, SHALL BE CONSTRUED AS A RECOMMENDATION FOR ITS USE IN INFRINGEMENT OF ANY EXISTING PATENT

US Polymers-Accurez, LLC | 300 East Primm Street | St. Louis, MO 63111 | 314-638-1632 | FAX 314-638-3100 | www.uspolymers.com