

HPP-1561-L

MODIFIED ALKYD FOR PVA PAINTS TO IMPROVE PROPERTIES

DESCRIPTION

The HPP 1561-L is a Plasticizer and Modifier for PVA Based Coatings to Improve Properties such as resistance to chalking. The HPP 1561-L is supplied at 99% Solids and is user friendly.

APPLICATIONS

Plasticizer and Modifier for PVA Paints to Improve Properties

FORM

Single Component, Modified Alkyd

OPERATING DATA

- 1) Engineered to be a modifier for PVA Coatings
- 2) Can be used at levels up to 40%

CAUTION

Agitate prior to use.

TYPICAL PROPERTIES

Viscosity (Gardner-Holt)	Z-Z2
Color	10 Max
Acid Value	10 Max
Solids (+/- 2)	99
Solvent	Xylene

PRECAUTIONS

Some materials in this product may cause skin and eye irritation and/or sensitization or other allergic responses upon repeated contact. Therefore this product must be handled with extreme care and in strict adherence to good industrial hygiene practices. Before using it or any other product referred to in this bulletin, consult the applicable Material Safety Data Sheets for appropriate handling procedures and protective equipment.

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, IS TO THE BEST OF OUR KNOWLEDGE TRUE AND ACCURATE. NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED IS MADE REGARDING THE PERFORMANCE OF ANY PRODUCT, SINCE THE MANNER OF USE IS BEYOND OUR CONTROL. NO SUGGESTION FOR PRODUCT USE, NOR ANYTHING HEREIN, SHALL BE CONSTRUED AS A RECOMMENDATION FOR ITS USE IN INFRINGEMENT OF ANY EXISTING PATENT

US Polymers-Accurez, LLC | 300 East Primm Street | St. Louis, MO 63111 | 314-638-1632 | FAX 314-638-3100 | www.uspolymers.com