

Valtex 184

OLEORESINOUS VARNISH

DESCRIPTION

Valtex 184 is a 1K System designed for sealing porous surfaces. The Valtex 184 was originally designed for Sheet Rock applications, but can be used for most substrates. Valtex 184 is non VT or Acrylic approach to a Stain-Killer and Sealer. Valtex 184 is low odor & would be ideal for Architectural Applications.

APPLICATIONS

Sealing Porous Surfaces/Vertical Applications

FORM

Single Component Air Dry Varnish to be used as a sealer for porous surfaces

OPERATING DATA

- 1) Designed for Most Applications Methods (Sray/Brush/Roll)
- 2) Imparts typical application and performance characteristics for Varnishes
- 3) Predictable drying characteristics

CAUTION

Agitate prior to use.

TYPICAL PROPERTIES

Viscosity (Gardner-Holt)	T-X
Color	11 Max
Acid Value	6 Max
Solids (+/- 2)	40
Solvent	Mineral Spirits

PRECAUTIONS

Some materials in this product may cause skin and eye irritation and/or sensitization or other allergic responses upon repeated contact. Therefore this product must be handled with extreme care and in strict adherence to good industrial hygiene practices. Before using it or any other product referred to in this bulletin, consult the applicable Material Safety Data Sheets for appropriate handling procedures and protective equipment.

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, IS TO THE BEST OF OUR KNOWLEDGE TRUE AND ACCURATE. NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED IS MADE REGARDING THE PERFORMANCE OF ANY PRODUCT, SINCE THE MANNER OF USE IS BEYOND OUR CONTROL. NO SUGGESTION FOR PRODUCT USE, NOR ANYTHING HEREIN, SHALL BE CONSTRUED AS A RECOMMENDATION FOR ITS USE IN INFRINGEMENT OF ANY EXISTING PATENT

US Polymers-Accurez, LLC | 300 East Primm Street | St. Louis, MO 63111 | 314-638-1632 | FAX 314-638-3100 | www.uspolymers.com