

Valtex 389

OLEORESINOUS WRINKLE VARNISH

DESCRIPTION

Valtex 389 is a 1K System designed for wrinkle applications. Valtex 389 can be used for both air dry or bake applications. Valtex 389 is low odor, excellent for single coat applications as well. Valtex 389 is most commonly used for metal applications.

APPLICATIONS

Wrinkle finish varnish

FORM

Single Component Air Dry or Baking Varnish for Wrinkle Finishes

OPERATING DATA

- 1) Designed for Most Application Methods (Sray/Dip/Brush/Roll)
- 2) Imparts typical application and performance characteristics for Varnishes
- 3) Predictable drying characteristics
- 4) Pigmented or Clear Applications

CAUTION

Agitate prior to use.

TYPICAL PROPERTIES

Viscosity (Gardner-Holt)	O-P
Color	11-13
Acid Value	-----
Solids (+/- 2)	63
Solvent	VM&P NAPTHA

PRECAUTIONS

Some materials in this product may cause skin and eye irritation and/or sensitization or other allergic responses upon repeated contact. Therefore this product must be handled with extreme care and in strict adherence to good industrial hygiene practices. Before using it or any other product referred to in this bulletin, consult the applicable Material Safety Data Sheets for appropriate handling procedures and protective equipment.

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, IS TO THE BEST OF OUR KNOWLEDGE TRUE AND ACCURATE. NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED IS MADE REGARDING THE PERFORMANCE OF ANY PRODUCT, SINCE THE MANNER OF USE IS BEYOND OUR CONTROL. NO SUGGESTION FOR PRODUCT USE, NOR ANYTHING HEREIN, SHALL BE CONSTRUED AS A RECOMMENDATION FOR ITS USE IN INFRINGEMENT OF ANY EXISTING PATENT

US Polymers-Accurez, LLC | 300 East Primm Street | St. Louis, MO 63111 | 314-638-1632 | FAX 314-638-3100 | www.uspolymers.com