

Valtex 577

OLEORESINOUS VARNISH FOR PASTE WOOD FILLERS AND CAULKING APPLICATIONS

DESCRIPTION

Valtex 577 is non-shrinking and stay liquid under the surface for extended amount of time. Valtex 577 is very low odor for interior and architectural type applications. Because of high solids and low viscosity, the Valtex 577 is excellent for high pigment loads, and lends itself to easy application uses. Valtex 577 wipes off easy and remains colorless.

APPLICATIONS

Paste Wood Filler / Caulking Products

FORM

Single Component Air Dry Varnish for Paste Wood Fillers and Caulking Agents

OPERATING DATA

- 1) Designed for Most Application Methods (Sray/Dip/Brush/Roll)
- 2) Imparts typical application and performance characteristics for Varnishes
- 3) Predictable drying characteristics yet remains liquid under the surface
- 4) Pigmented or Clear Applications

CAUTION

Agitate prior to use.

TYPICAL PROPERTIES

Viscosity (Gardner-Holt)	A4
Color	18 Max
Acid Value	13-18
Solids (+/- 2)	58
Solvent	Mineral Spirits

PRECAUTIONS

Some materials in this product may cause skin and eye irritation and/or sensitization or other allergic responses upon repeated contact. Therefore this product must be handled with extreme care and in strict adherence to good industrial hygiene practices. Before using it or any other product referred to in this bulletin, consult the applicable Material Safety Data Sheets for appropriate handling procedures and protective equipment.

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, IS TO THE BEST OF OUR KNOWLEDGE TRUE AND ACCURATE. NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED IS MADE REGARDING THE PERFORMANCE OF ANY PRODUCT, SINCE THE MANNER OF USE IS BEYOND OUR CONTROL. NO SUGGESTION FOR PRODUCT USE, NOR ANYTHING HEREIN, SHALL BE CONSTRUED AS A RECOMMENDATION FOR ITS USE IN INFRINGEMENT OF ANY EXISTING PATENT

US Polymers-Accurez, LLC | 300 East Primm Street | St. Louis, MO 63111 | 314-638-1632 | FAX 314-638-3100 | www.uspolymers.com