

## **Valtex 82**

### **OLEORESINOUS VARNISH**

#### **DESCRIPTION**

Highly unique 1K Primer for Steel Ship Hulls. The 1K System produces excellent chemical, corrosion, alkali, and acid resistance. For 1K Systems, this product is the best for the environments. Valtex 82 is designed for under the water line anti-fouling. Valtex 82 is long lasting. Excellent counter offering against 2K Epoxy Systems.

#### **APPLICATIONS**

Cruise/Cargo Ship Hulls, Bridges, Dams, Locks, Storage Tanks

#### **FORM**

Single Component, Pigmented, DTM, Primer can be used with Zinc

#### **OPERATING DATA**

- 1) Designed for Most Application Methods
- 2) TTP 641- TYPE 3 & MIL-V-15218-A TYPE 3
- 3) Highly efficient at thin coat weight v/s 2K Epoxies
- 4) Predictable drying characteristics

#### **CAUTION**

Agitate prior to use.

#### **TYPICAL PROPERTIES**

<b>Viscosity (Gardner-Holt)</b> .....	<b>F-H</b>
<b>Color</b> .....	<b>17 Max</b>
<b>Acid Value</b> .....	<b>-----</b>
<b>Solids (+/- 2)</b> .....	<b>55</b>
<b>Solvent</b> .....	<b>61% A100 / 39% Xylene</b>

#### **PRECAUTIONS**

Some materials in this product may cause skin and eye irritation and/or sensitization or other allergic responses upon repeated contact. Therefore this product must be handled with extreme care and in strict adherence to good industrial hygiene practices. Before using it or any other product referred to in this bulletin, consult the applicable Material Safety Data Sheets for appropriate handling procedures and protective equipment.

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, IS TO THE BEST OF OUR KNOWLEDGE TRUE AND ACCURATE. NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED IS MADE REGARDING THE PERFORMANCE OF ANY PRODUCT, SINCE THE MANNER OF USE IS BEYOND OUR CONTROL. NO SUGGESTION FOR PRODUCT USE, NOR ANYTHING HEREIN, SHALL BE CONSTRUED AS A RECOMMENDATION FOR ITS USE IN INFRINGEMENT OF ANY EXISTING PATENT

US Polymers-Accurez, LLC | 300 East Primm Street | St. Louis, MO 63111 | 314-638-1632 | FAX 314-638-3100 | [www.uspolymers.com](http://www.uspolymers.com)