

Valtex 865

OLEORESINOUS VARNISH FOR CAULKING APPLICATIONS

DESCRIPTION

Valtex 865 is designed strictly for caulking products (i.e. it makes putty). Valtex 865 has excellent adhesion properties to wood. It will not deteriorate the substrate versus other products in the market place. The product is very user friendly for DIY and Contractor business. Valtex 865 is long lasting as well.

APPLICATIONS

Paste Wood Filler / Caulking Products

FORM

Single Component Air Dry Varnish for Caulking Agents

OPERATING DATA

- 1) Imparts friendly and easy to use application methods
- 2) Imparts typical application and performance characteristics for Varnishes
- 3) Predictable drying characteristics yet remains liquid under the surface
- 4) Pigmented or Clear Applications

CAUTION

Agitate prior to use.

TYPICAL PROPERTIES

Viscosity (Gardner-Holt)	F-G
Color	13 Max
Acid Value	-----
Solids (+/- 2)	55
Solvent	Mineral Spirits

PRECAUTIONS

Some materials in this product may cause skin and eye irritation and/or sensitization or other allergic responses upon repeated contact. Therefore this product must be handled with extreme care and in strict adherence to good industrial hygiene practices. Before using it or any other product referred to in this bulletin, consult the applicable Material Safety Data Sheets for appropriate handling procedures and protective equipment.

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, IS TO THE BEST OF OUR KNOWLEDGE TRUE AND ACCURATE. NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED IS MADE REGARDING THE PERFORMANCE OF ANY PRODUCT, SINCE THE MANNER OF USE IS BEYOND OUR CONTROL. NO SUGGESTION FOR PRODUCT USE, NOR ANYTHING HEREIN, SHALL BE CONSTRUED AS A RECOMMENDATION FOR ITS USE IN INFRINGEMENT OF ANY EXISTING PATENT

US Polymers-Accurez, LLC | 300 East Primm Street | St. Louis, MO 63111 | 314-638-1632 | FAX 314-638-3100 | www.uspolymers.com