HPP 7602

Polyester Resin

HPP 7602 is designed to be used to plasticize nitrocellulose for fingernail polish applications.

Physical State
Liquid

Applications
- Nail Polish

Advantages
- Excellent Gloss
- Good Durability

Typical Properties

Viscosity (Gardner-Holdt)	**Y – Z3**
Color (Gardner)	**2 max.**
Acid Value	**60 mg KOH/g max.**
Solids	**70 ± 2%**
Density	**9.00 ± 0.15 lb/gal**
Solvent	**95% Ethanol**
	5% Isopropanol
HEW	**310.4**

US POLYMERS-ACCUREZ
SPECIALTY CHEMICALS

Shelf Life: 2 years in a sealed container at 77°F.
When container is opened, it must be nitrogen blanketed or it will skin.

Precautions
Some materials in this product may cause skin and eye irritation and/or sensitization or other allergic responses upon repeated contact.Therefore, this product must be handled with extreme care and in strict adherence to good industrial practices. Before using it or any other product referred to in this bulletin, consult the applicable Safety Data Sheets for appropriate handling procedures and protective equipment.

Revision Date: Sept 1, 2026

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, IS TO THE BEST OF OUR KNOWLEDGE TRUE AND ACCURATE. NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIEDIS MADE REGARDING THE PERFORMANCE OF ANY PRODUCT, SINCE THE MANNRT OF USE IS BEYOND OUR CONTROL. NO SUGGESTION FOR PRODUCT USE, NOR ANYTHING HEREIN, SHALL BE CONSTRUED AS A RECOMMENDATION FOR ITS USE IN INFRINGEMENTOF ANY EXISTING PATENT

300 East Primm St. | St. Louis, MO 63111 | (314) 638-1632 | Fax: (314) 638-3100 |
www.uspolymers.com