LA-7376

Hydroxy Functional Polyester

LA-7376 is a hydroxy functional polyester designed for melamine baking systems. A crosslinker is recommended.

Physical State
Liquid

Applications

- Baking Systems

Operating Data:

1. Designed for spray and roller applications.
2. Reduce viscosity as needed for roll or spray.
3. Must be neutralized and diluted in water.
4. TEA or DMEA may be used in a bake system.

Typical Properties

Viscosity (Gardner-Holdt)	**V - Y**
Color (Gardner)	**3 max.**
Acid Value	**60- 75 mg KOH/g**
Solids	**60 ± 2%**
Density	**8.85 ± 0.15 lb/gal**
Solvent	**DMM Dipropylene Glycol Dimethyl ether**
HEW	**440**

Shelf Life: 2 years in a sealed container at 77°F.

Revision Date: 9/1/2026

Precautions
Some materials in this product may cause skin and eye irritation and/or sensitization or other allergic responses upon repeated contact. Therefore, this product must be handled with extreme care and in strict adherence to good industrial practices. Before using it or any other product referred to in this bulletin, consult the applicable Safety Data Sheets for appropriate handling procedures and protective equipment.

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, IS TO THE BEST OF OUR KNOWLEDGE TRUE AND ACCURATE. NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED IS MADE REGARDING THE PERFORMANCE OF ANY PRODUCT, SINCE THE MANNRT OF USE IS BEYOND OUR CONTROL. NO SUGGESTION FOR PRODUCT USE, NOR ANYTHING HEREIN, SHALL BE CONSTRUED AS A RECOMMENDATION FOR ITS USE IN INFRINGEMENTOF ANY EXISTING PATENT

300 East Primm St. | St. Louis, MO 63111 | (314) 638-1632 | Fax: (314) 638-3100 | www.uspolymers.com