LA-8850

Long Oil Alkyd

LA-8850 is a long oil alkyd designed as a flexible coating. It has excellent impact resistance for an alkyd type vehicle. LA-8850 is most used over substrates which require only one coat of durable resin-coating system. LA-8850 will make excellent aluminum vehicles. This works especially well when combined with one of our tung oil-phenolic varnishes. This product is listed on the DSL/NDSL inventory.

Physical State
Liquid

Applications
- Aluminum Vehicle
- Substrates w/ One Coat of Durable Resin Coating
- Low Odor Architectural

Advantages
- Low Odor
- Flexible
- Excellent Impact Resistance

Typical Properties

Viscosity (Gardner-Holdt)	**Z7 – Z8**
Color (Gardner)	**6 max.**
Acid Value	**10 mg KOH/g max.**
Solids	**70 ± 2%**
Density	**7.70 ± 0.15 lb/gal**
Solvent	**Isopar™ L**

Recommended Driers (Metal on resin solids):
Air Dry: 0.2% - 12% Zirconium
0.1% - 12% Cobalt

Shelf Life: 2 years in a sealed container at 77°F.

Precautions
Some materials in this product may cause skin and eye irritation and/or sensitization or other allergic responses upon repeated contact. Therefore, this product must be handled with extreme care and in strict adherence to good industrial practices. Before using it or any other product referred to in this bulletin, consult the applicable Safety Data Sheets for appropriate handling procedures and protective equipment.

Revision Date: Sept 1, 2026

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, IS TO THE BEST OF OUR KNOWLEDGE TRUE AND ACCURATE. NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED IS MADE REGARDING THE PERFORMANCE OF ANY PRODUCT, SINCE THE MANNRT OF USE IS BEYOND OUR CONTROL. NO SUGGESTION FOR PRODUCT USE, NOR ANYTHING HEREIN, SHALL BE CONSTRUED AS A RECOMMENDATION FOR ITS USE IN INFRINGEMENTOF ANY EXISTING PATENT

300 East Primm St. | St. Louis, MO 63111 | (314) 638-1632 | Fax: (314) 638-3100 | www.uspolymers.com