LA-9158

Aliphatic Hydroxy Functional Polyester

LA-9158 is an innovative saturated polyester polyol designed to be crosslinked with polyisocyanates at room temperature to produce high performance finished coatings. These coatings possess excellent gloss and gloss retention, superior QUV resistance as well as fantastic chemical and scratch/abrasion resistance. Finished coatings based on LA-9158 also possess outstanding hardness development.

Physical State
Liquid

Applications
- High Traffic Floor Coatings
- Transportation Coatings

Advantages
- Excellent Gloss Retention
- Light Stability
- Good Chemical Resistance
- Good Abrasion Resistance
- Outstanding Hardness Development

Operating Data
1. Designed for brush, spray, and roller applications.
2. Reduce viscosity as needed for roll or spray.

Typical Properties

Viscosity (Gardner-Holdt)	**Z4 – Z6**
Color (Gardner)	**2 max.**
Acid Value	**6 mg KOH/g max.**
Solids	**75 ± 2%**
Density	**9.25 ± 0.15 lb/gal**
Solvent	**PM Acetate**
HEW	**230**

Shelf Life: 2 years in a sealed container at 77°F.

Precautions
Some materials in this product may cause skin and eye irritation and/or sensitization or other allergic responses upon repeated contact. Therefore, this product must be handled with extreme care and in strict adherence to good industrial practices. Before using it or any other product referred to in this bulletin, consult the applicable Safety Data Sheets for appropriate handling procedures and protective equipment.

Revision Date: Sept 1, 2026

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, IS TO THE BEST OF OUR KNOWLEDGE TRUE AND ACCURATE. NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED IS MADE REGARDING THE PERFORMANCE OF ANY PRODUCT, SINCE THE MANNER OF USE IS BEYOND OUR CONTROL. NO SUGGESTION FOR PRODUCT USE, NOR ANYTHING HEREIN, SHALL BE CONSTRUED AS A RECOMMENDATION FOR ITS USE IN INFRINGEMENTOF ANY EXISTING PATENT

300 East Primm St. | St. Louis, MO 63111 | (314) 638-1632 | Fax: (314) 638-3100 | www.uspolymers.com