Valtex 327-55

Medium Long Oil Varnish

Valtex 327-55 is a medium long oil varnish for interior and exterior applications. This is an air-dry system which will enhance the properties of a coating. Valtex 327-55 will improve water, chemical, and abrasion resistance.

Applications:

Aluminum Leafing

- Paints (Interior & Exterior)
- Barn Roofs
- Chain Link Paste

Wood Surfaces

- Utility Varnish

Advantages:

- Water Resistance
- Chemical Resistance
- Abrasion Resistance
- Economical

Operating Data

1. Designed for brush, spray, and roller applications
2. Reduce viscosity as needed for roll or spray
3. 10 cc per gallon of skinning agent is recommended (ASA)
4. Predictable drying characteristics
5. For best results in areas of high exposure to sunlight we recommend the addition of ultraviolet absorbers

Typical Properties

Viscosity (Gardner-Holdt)	**H - I**
Color (Gardner)	**12 max.**
Acid Value	**10 mg KOH/g max.**
Solids	**55 ± 2%**
Density	**7.30 ± 0.15 lb/gal**
Solvent	**Mineral Spirits**

Recommended Driers (Based on metal solids & on resin solids)

0.05% Cobalt
0.02% Zirconium

Shelf Life: 2 years in a sealed container at 77°F.
When container is opened, it must be nitrogen blanketed or it will skin.

Revision Date: 9/1/2026

Precautions

Some materials in this product may cause skin and eye irritation and/or sensitization or other allergic responses upon repeated contact. Therefore, this product must be handled with extreme care and in strict adherence to good industrial practices. Before using it or any other product referred to in this bulletin, consult the applicable Safety Data Sheets for appropriate handling procedures and protective equipment.

THE INFORMATION PRESENTED HEREIN, WHILE NOT GUARANTEED, IS TO THE BEST OF OUR KNOWLEDGE TRUE AND ACCURATE. NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED IS MADE REGARDING THE PERFORMANCE OF ANY PRODUCT, SINCE THE MANNRT OF USE IS BEYOND OUR CONTROL. NO SUGGESTION FOR PRODUCT USE, NOR ANYTHING HEREIN SHALL BE CONSTRUED AS A RECOMMENDATION FOR ITS USE IN INFRINGEMENTOF ANY EXISTING PATENT

300 East Primm St. | St. Louis, MO 63111 | (314) 638-1632 | Fax: (314) 638-3100 | www.uspolymers.com